



QWIK JON® PREMIER MODEL #201

**QUICK REFERENCE GUIDE.
SEE INSTRUCTION MANUAL FOR
COMPLETE DETAILS.**

<https://zh-cn.zoellerpumps.com/>
<https://zoellerpumps.com/>



1 Connect the rear discharge toilet to the front inlet of the Qwik Jon® Premier. Ensure the connections are in accordance with local, regional, and state codes.



2 Connect the drain pipe from another bathroom fixture to the side inlet on the Qwik Jon® Premier. Notice the side inputs have built in check valves and are compatible with many piping sizes. The pipe adaptor needs to be cut in the center. Ensure the connections are in accordance with local, regional, and state codes.



3 Connect the discharge pipe to the top of the Qwik Jon® Premier.



4 The Qwik Jon® Premier has an inlet on either side allowing side inlet connections from other bathroom fixtures.



5 Plug the power cord into a wall socket to provide power to the unit.



FIRE/EXPLOSION HAZARD.

Do not pump flammable or explosive fluids such as gasoline, fuel oil, kerosene, etc. Do not use in a flammable and/or explosive atmosphere. Failure to follow these warnings could result in death or serious injury and/or property damage.

**These drawings are for reference only.
Exact components may differ by region.**



QWIK JON® PREMIER
MODEL #201

快速安装说明

如需要完整细节，请见安装手册。
<https://zh-cn.zoellerpumps.com/>
<https://zoellerpumps.com/>



1 请将后排式马桶连接到Qwik Jon® Premier前方面入水口，请确保安装条件符合当地建筑法规。



2 您可将其他卫浴设备的排水管连接至Qwik Jon® Premier两侧入水口，请注意Qwik Jon® Premier两侧入水口备有内建式止回阀，并且可以搭配多种尺寸。快速活接中间部分需切除。确保连接符合当地法规要求。



3 将排水管连接到Qwik Jon® Premier上方出水口接头。



4 Qwik Jon® Premier提升器两侧备有侧入水口，可连结其他卫浴设备。



5 确定入水，出水管安装无误后将提升器插头连接至墙上电源插座。



火灾/爆炸危险提醒

请勿将泵送易燃或易爆液体，例如汽油、燃料油及煤油等。

请勿再易燃和/或易爆性的环境中使用。

如不遵守这些警告可能会导致死亡或重伤和/或财产损失。

以上图面仅供参考，配置将因不同国家或区域而有所不同。